

Specifications Model: C61S

System	Operation system	Embedded Linux OS
	Online visitor	Support 4 visitors at the same time
Image Capture	Image sensor	1/2.4 inch 1080p Progressive Scan CMOS sensor
	Minimum Illumination	0.3-0.5Lux(color mode), 0 Lux(B&W mode)
	Lens	2.4mm@F2.4
	View Angle	1360°
	Night vision	Automatic switching of dual filters, 3pcs 850nm patch infrared lamps, IR irradiation distance:5-10m
Video	Encode format	H.264 main profile/H.264+ main profile/Motion-JPEG/JPEG
	Streams	Main stream: 1536*1536@20fps Sub stream: 320*320@20fps
	Bit Rate/Max Fps	128~4096kbps/20pfs
	Image adjustment	Brightness and contrast can be adjusted
Audio	Input	Built-in—38±5dB microphone
	Output	8Ω 1W speaker
	Sampling frequency /Bit width	8KHz/16bit
	Compression standard /code rate	ADPCM/32kbps
Network	Ethernet	10Mbps/100Mbps adaptive /RJ45 interface
	Protocols	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc.
	Wireless LAN	IEEE802.11b/g/n, Support AP mode
	Wireless LAN Frequency	2.4~ 2.4835GHz
	Wireless LAN security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
Memory	Socket	TF Push-push socket,Maximum support 256GB, cloud storage, NVR, NAS
Alarm	Alarm Trigger	Motion detection
Physical Environmental	Rated voltage	DC12V±5%@DC
	Power consumption	Rated power: 6.3W (with infrared lights on)
	Operating condition	Temperature:-10~50℃,humidity:<90%
	Weight	Net: 241.7g Gross: 473.7 g(Note: in kind prevail)
	Package size	196x183x110mm (L×W×H)